

Busbar Systems



10/2	Introduction
10/3	General data
10/7 10/8	8US 40 mm busbar systems Introduction Basic assemblies up to 400 A
10/9 10/10 10/14 10/15 10/18 10/25 10/26 10/29	8US 60 mm busbar systems Introduction Basic assemblies up to 630 A Basic assemblies up to 1 600 A Infeed and connection methods from 630 A to 1 600 A Busbar device adapters and device holders from 630 A to 1 600 A Connection of 3NP1 fuse switch disconnectors UL applications Accessories
10/31	Distribution board components
10/33	Built-in components

For further technical product information:

Configuration Manual

8US Busbar Systems 2014
Article No.: 3ZW1012-8US10-0AC1

Service & Support Portal







www.siemens.com/lowvoltage/product-support

→ Product List:
Technical specifications

→ Entry List:
Certificates / Characteristics /
Download / FAQ / Manuals /
Updates

Introduction


Overview

Devices		Page	Application	Standards	Used in		
					Non-residential buildings	Residential buildings	Industry
	8US 40 mm busbar systems	10/7	Basic assemblies up to 400 A, busbar supports, busbars, covers for the touch protection	EN 13601 IEC 60439-1, IEC 61439-2	✓	--	✓
 NSE0_02112	Basic assemblies up to 400 A	10/8	Basic assemblies up to 400 A, busbar supports, busbars, covers for the touch protection	EN 13601 IEC 60439-1, IEC 61439-2	✓	--	✓
	8US 60 mm busbar systems	10/9	Basic assemblies up to 630 A, overview with different devices	EN 13601 IEC 60439-1, IEC 61439-2 UL 508 A	✓	--	✓
 NSE0_02123	Basic assemblies up to 630 A	10/10	Basic assemblies up to 630 A, busbar supports, busbars, covers for the touch protection	EN 13601 IEC 60439-1, IEC 61439-2 UL 508 A	✓	--	✓
 NSE0_02113	Basic assemblies up to 1 600 A	10/14	Basic assemblies up to 1 600 A, busbar supports, busbars, covers for the touch protection	EN 13601 IEC 60439-1, IEC 61439-2 UL 508 A	✓	--	✓
	Infeed and connection methods from 630 A to 1 600 A	10/15	Infeed for busbar systems, terminals...	EN 13601 IEC 60439-1, IEC 61439-2 UL 508 A	✓	--	✓
	Busbar device adapters and device holders from 630 A to 1 600 A	10/18	Busbar device adapters and device holders for the assembly of load feeders 3RV2/3RT2	EN 13601 IEC 60439-1, IEC 61439-2 UL 508 A	✓	--	✓
	Distribution board components	10/31	Longitudinal stays, assembly kits, covers for the touch protection	IEC 60439-1, IEC 61439-3 VDE 0603-1	✓	--	✓
	Built-in components	10/33	3-pole NEOZED bus-mounting bases or DIAZED bus-mounting bases, NEOZED bus-mounting switch disconnectors, fuse switch disconnectors and busbar device adapters	IEC 60947-3, EN 60947-3 (VDE 0660) IEC 60269, EN 60269 (VDE 0636)	✓	--	✓

Overview

The use of busbar systems with their versatile rail-adaptable connection, switching and installation devices is an ideal and cost-effective electrotechnical enhancement of modern distribu-

tion boards due to their small footprint, compact design and quick assembly contacts. Mounting is implemented on longitudinal stays. The busbar spacing is 60 mm.



Benefits

Notable cost reduction compared to conventional installation in switchgear and control cabinets due to the following reasons:

- Mechanical fixing and electrical contacting in a single step
- No access wiring and fewer busbar terminals used
- Double use of the busbar space
- Clear arrangement
- Straightforward replacement of individual devices or whole combinations
- High operational safety through finger-safe cover of the adapters and device holders

All the above advantages are felt especially in cases where many tap-off units of the same performance range are required.

Application

8US busbar systems are used for the direct busbar-mounting of current-limiting devices (protective devices) such as fuse switch disconnectors and circuit breakers as well as complete load feeders.

8US busbar systems are designed for horizontal mounting of the busbars.

Design

8US busbar systems with 60 mm busbar center-to-center spacing as well as flat copper profiles have become firmly established on the world market.

The permissible busbar temperature is decisive when dimensioning the busbars. The busbar temperature is dependent on the current and the current distribution, on the busbar cross-section and the busbar surface, on the position of the busbars, convection and the ambient temperature. The values stated in the following table can only be considered as guide values because the conditions vary with each location. The values are based on continuous current over the whole busbar length.

The busbar runs prove most advantageous when the infeed is centrally located and the load is distributed symmetrically on both sides.

Function

Short-circuit strength

The short-circuit strength of the busbar system is dependent on the distance of the busbar supports and on the busbar cross-section.

The short-circuit strength of the whole system is dependent on the short-circuit strength of the busbars and of the adapters with circuit breakers or switch disconnectors. If one of these values is lower than the prospective short-circuit current at the installation site, a current-limiting protective device has to be mounted upstream of the 8US busbar system. This may also be mounted as a feeder circuit breaker on the busbar system itself.

General data

Technical specifications

Continuous current for busbars, E-Cu bare, at 35 °C ambient temperature according to DIN 43671

Bar dimensions mm	System mm	Continuous current at a busbar temperature of		
		65 °C A	85 °C A	105 °C A
12 × 5	40 + 60	188	248	295
15 × 5	40 + 60	222	293	349
20 × 5	60	274	362	430
25 × 5	60	327	432	513
30 × 5	60	379	500	595
12 × 10	40 + 60	302	398	474
20 × 10	60	427	564	670
30 × 10	60	573	756	900
Special profile up to 1 600 A	60	1 020	1 020	1 600

General technical specifications

Rated insulation voltage U_i	V AC	1 000
Short-circuit strength of 8US1 busbar device adapter		Current limitation due to associated motor starter protectors/circuit breakers/load feeders up to 50 kA see Characteristic Curves
of the busbar systems		
Material of the 8US1 busbar supports, busbar device adapters and device holders		Glass-fiber reinforced polyamide
Color		RAL 7035, light gray
Thermal stability (minimum values)		
Busbar supports, busbar device adapters, device holders, infeed and caps	°C	120
AWG connecting cables	°C	105 / 150
Cover profiles	°C	110
Bases, partitions, edge profiles and blanking covers	°C	70
Machining of plastic profiles		Take care when machining that no cracks are formed. A cross-cut circular saw with the following characteristic values has proven successful in cutting cover profiles for busbars: • D = 300 mm, B = 2.2 mm, • T = 120 R (5° negative replaceable tooth at a cutting rate of 50 ... 60 m/s) • Tooth feed 0.05 ... 0.1 mm The plastic parts are secured so that vibration is ruled out.
Approvals Busbar supports, busbar device adapters, device holders and terminals		UR, CSA, cULus- Listed


Technical specifications of the system components

Infeed, connection modules, three-phase		5SH3538	5SH3535	8US1921-1BA00	8US1921-1AA00
Busbar center-to-center spacing	mm	60	60	60	60
Current carrying capacity of the terminal points The specified current carrying capacities reflect the thermal load capability of the terminal points under favorable conditions (with the largest conductors it is possible to connect). This does not invalidate the assignment of conductor cross-sections and current carrying capacities as defined in national and international specifications.	A	80	560	300	440
Tightening torque	Nm	--	30	8 ... 10	12 ... 15
Clamping space W × H	mm	--	--	10 × 15	15 × 15
Conductors that can be used	mm ²	1.5 ... 16 Cu, re, rm, f, f+AE (reduction of the maximum conductor cross-sections may be required)	150 ... 300 Cu, Al (connections with aluminum conductors are not maintenance free), rm, sm, f	6 ... 50 (70) Cu, rm, f, f+AE (reduction of the maximum conductor cross-sections may be required), la. Cu 6 × 9 × 0.8	35 ... 120 Cu, rm, f, f+AE (reduction of the maximum conductor cross-sections may be required), la. Cu 6/10 × 15.5 × 0.8


Characteristic curves

Characteristic curves as a function of rated peak withstand current


40 mm busbar systems




60 mm busbar systems



100 mm busbar systems



185 mm busbar systems



General data

Current-carrying capacity values for flat bars acc. to DIN 43671

According to DIN 43671, current-carrying capacity values for flat bars are defined as 35 °C ambient temperature and 65 °C busbar temperature.

If a higher bar temperature than 65 °C is possible, the busbars can be operated with higher current values according to the following formula: $I = I_n \cdot k_2$

Example

Under normal operating conditions (35 °C ambient temperature and 65 °C bar temperature), a 30 x10 mm busbar can handle loads up to 630 A. However, you want the busbar to handle a higher current, at the expense of an increased busbar temperature of max. 85 °C.


The following applies:

- Bar type: Busbar
- Busbar size: 30 x 10
- Max. bar temperature: 85 °C
- Ambient temperature: 35 °C

The figure on the right shows the correction factor $k_2 = 1.3$ for the current-carrying capacity.

This results in a higher value of $630 \text{ A} \cdot 1.3 = 819 \text{ A}$.

If the 30 x10 busbar is to be operated with a bar temperature of 85 °C, it may be loaded with maximum 819 A.



Current-carrying capacity values for 30 x 10 mm flat bars acc. to DIN 43671, depending on ambient and bar temperature

Overview



The 40 mm busbar system for the lower performance range up to 400 A: Terminals and covers for infeed and connection methods

The 40 mm busbar system is used in machine engineering and distribution boards, in meter cabinets and in power distribution systems of the low performance range up to 400 A.

The busbar cross-sections are adapted to the rated currents and are available in the sizes 12 x 5 mm, 12 x 10 mm, 15 x 5 mm and 15 x 10 mm. The basic system is configured without covers. If touch protection is required, this is possible with busbar covers.


Terminals round off the product range of the 40 mm busbar system.

Busbar Systems

8US 40 mm Busbar Systems

Basic assemblies up to 400 A

Overview



40 mm busbar system: Basic assembly up to 400 A

Selection and ordering data

	Description	DT	Article No.	Price per PU	PU (UNIT, SET, M)	PS*/P. unit	PG	Weight per PU approx. kg
 8US1903-3AB00  8US1903-5AA00  8WC5  8US1922-2CA00	②④⑤ Busbar supports End and intermediate holders for flat copper profiles 12 mm x 5 mm, 12 mm x 10 mm, 15 mm x 5 mm, 15 mm x 10 mm 3-pole, with inside fixing (PU = 2 busbar supports including inlay parts for bar thickness 5 mm and lateral finger-safe covers)		8US1903-3AB00		1	1 unit	143	0.186
	5-pole, 12 mm x 5 mm and 12 mm x 10 mm with inside fixing	L1-L3 + N + PE/N	8US1903-5AA00		1	1 unit	143	0.155
	① Flat copper profiles (flat profile, approx. 2.4 m long, bare, according to EN 12167) 12 mm x 5 mm 15 mm x 5 mm		8WC5123 8WC5121		1 1	1 unit 1 unit	143 143	1.100 1.550
	③ Cover profiles for busbars 12 mm x 5 mm 1000 mm long 15 mm x 5 mm 1000 mm long		8US1922-2CA00 8US1922-2AA00		1 1	10 units 10 units	143 143	0.066 0.153

Overview



The 60 mm busbar system for the medium and top performance range up to 1 600 A, here for example with the 3NP1 switch disconnector, size 3

The 60 mm busbar system is used preferably in control cabinet installation, in motor control centers and in power distribution systems of the medium power range (630 A) and top performance range (1 600 A, special profile).

The 60 mm busbar system can be configured as a basic system without covers. The busbar cross-sections are available in the sizes 12 x 5 mm to 30 x 10 mm and as a special profile.

Busbar adapters for SIRIUS, 3VL circuit breakers, 3KA and 3KL switch disconnectors, and 3NP1 and 3NP5 fuse switch disconnectors offer numerous options for configuring this busbar system. Infeed units, terminals and other accessories open up a large range of applications.

Busbars with a special profile are suitable for applications up to 1 600 A. All components of the 60 mm busbar system can be fitted.

SIRIUS motor starter combinations

SIRIUS motor starter combinations can be configured with and without fuses.

The compact 3NW7...-1 cylindrical fuse holders for IEC fuses, size 10x38 mm, or 3NW7...-1HG UL for Class CC fuses are suitable for use with fused motor starter combinations.

With a width of 45 mm, SIRIUS motor starter combinations are the same width as the majority of contactors.

For further information and accessories, [see chapter 5, "Fuse Systems" → Cylindrical fuse systems](#)
 → Fuse holders in size 10x38 mm and Class CC.




Installation configuration of a cylindrical fuse holder and a SIRIUS contactor on busbar device adapter for the 60 mm busbar system

Busbar Systems

8US 60 mm Busbar Systems

Basic assemblies up to 630 A



Overview



60 mm busbar system: Basic assemblies up to 630 A

Selection and ordering data

Longitudinal stays and assembly kits for ALPHA distribution boards

	Description	Dimensions	DT	Article No.	Price per PU	PU (UNIT, SET, M)	PS*/P. unit	PG	Weight per PU approx.
		mm							kg
	Longitudinal stays								
	For mounting the assembly kits in unequipped distribution boards, two longitudinal stays are required for each assembly kit width								
		Height							
		600		8GK4851-4KK00		1	1 set	039	0.838
		750		8GK4851-5KK00		1	1 set	039	1.076
		900		8GK4851-6KK00		1	1 set	039	1.302
		1050		8GK4851-7KK00		1	1 set	039	1.528
	Assembly kits								
	Comprising touch protection cover and 4 supports								
	Cutout width for three-phase busbar systems								
	• 216 mm	300 × 250		8GK4801-2KK13		1	1 unit	039	0.500
	• 466 mm	300 × 500		8GK4801-2KK23		1	1 unit	039	0.700
	• 716 mm	300 × 750		8GK4801-2KK33		1	1 unit	039	0.900
	• 216 mm	450 × 250		8GK4801-3KK13		1	1 unit	039	0.650
	• 466 mm	450 × 500		8GK4801-3KK23		1	1 unit	039	0.900
	• 716 mm	450 × 750		8GK4801-3KK33		1	1 unit	039	1.150
	1 set = 2 stays								

Busbar Systems

8US 60 mm Busbar Systems

Basic assemblies up to 630 A

Busbar support and end cover

	Description	Connections	Standard	DT	Article No.	Price per PU	PU (UNIT, SET, M)	PS*/ P. unit	PG	Weight per PU approx. kg
② Busbar supports										
End and intermediate holders for flat copper profiles 12, 15, 20, 25, 30 x 5, 10 mm										
	3-pole, with outside fixing	L1-L3			8US1923-2AA01		1	10 units	143	0.161
	3-pole, with inner fixing	L1-L3			8US1923-3AA01		1	10 units	143	0.155
	4-pole, with inner fixing	L1-L3 + PE/N			8US1923-4AA00		1	10 units	143	0.244
	2-pole, with outside fixing				8US1923-5AA00		1	10 units	143	0.112
N/PE busbar supports 12, 20, 30 x 5, 10 mm										
	1-pole, for flat copper profile for 5/10 mm busbars	PE/N			5SH3540		1	1 unit	031	0.059
N/PE busbar supports 6 x 6 mm 12, 15, 20, 25, 30 x 5, 10 mm										
	1-pole, for copper profiles for mounting on 8US1923-2AA01 3-pole busbar supports or free standing	PE/N	UL508		8US1923-1AA01		1	1 unit	143	0.039

Busbar Systems

8US 60 mm Busbar Systems

Basic assemblies up to 630 A

	Description	Connections	Standard	DT	Article No.	Price per PU	PU (UNIT, SET, M)	PS*/ P. unit	PG	Weight per PU approx. kg
	End and intermediate holders for flat copper profiles 5 mm x 20 mm, 10 mm x 20 mm, 10 mm x 30 mm				8US1923-3UA01		1	10 units	143	0.126
	3-pole, with inner fixing	L1-L3	UL 508 ¹⁾							
8US1923-3UA01										
	③ End covers For covering free busbar ends For 8US1923-2AA01, 3AA01 and -3UA01				8US1922-1AC00		1	10 units	143	0.020
		L1-L3	UL 508							
8US1922-1AC00										

Covers, supports for blanking covers, flat copper profiles and busbar connection parts

	Description	Length	Width	Standard	DT	Article No.	Price per PU	PU (UNIT, SET, M)	PS*/ P. unit	PG	Weight per PU approx.
		mm	mm								kg
 8US1922-2CA00	④ Cover profiles for busbars					8US1922-2CA00		1	10 units	143	0.066
	12 mm x 5 mm	1000									
	15 mm x 5 mm, 20 mm x 5 mm, 25 mm x 5 mm, 30 mm x 5 mm	1000	UL 508								
	12 mm x 10 mm, 15 mm x 10 mm, 20 mm x 10 mm, 25 mm x 10 mm, 30 mm x 10 mm	1000	UL 508								
 8US1922-2AA00	⑤ Supports for blanking covers					8US1922-2EA00		1	4 units	143	0.035
	Mounting on busbar, 32 mm depth (2 units per section of blanking cover)		UL 508								
 8US1922-2EA0.						8US1922-2EA01		1	8 units	143	0.081
	Mounting on busbar, 107 mm depth (2 units per section of blanking cover)		UL 508								
 8US1922-2EB00	⑥ Blanking covers					8US1922-2EB00		1	2 units	143	0.700
	Mounting on 8US1922-2EA.. support for blanking covers Height 195 mm, Depth 63 mm, Length 700 mm		UL 508								

¹⁾ Only with base plate 8US1922-2UA01

Busbar Systems

8US 60 mm Busbar Systems

Basic assemblies up to 630 A


	Description	Length mm	Cross- section mm ²	Standard	DT	Article No.	Price per PU	PU (UNIT, SET, M)	PS*/ P. unit	PG	Weight per PU approx. kg
	Base plates										
	For 3-pole system, width 230 mm	1100	--	UL 508		8US1922-2UA01		1	2 units	143	0.600
① Flat copper profiles (flat profile, bare)											
Flat copper profiles for universal applications											
	• 12 x 5 mm, current intensity 200 A	2400	60	EN 12167		8WC5123		1	1 unit	143	1.100
	• 15 x 5 mm, current intensity 250 A	2400	75	EN 12167		8WC5121		1	1 unit	143	1.550
	• 20 x 5 mm, current intensity 320 A	2400	100	EN 12167		8WC5126		1	1 unit	143	1.780
	• 20 x 5 mm, current intensity 400 A	1100	125	EN 12167		8WC5031-1AA00		1	1 unit	143	2.240
	• 25 x 5 mm, current intensity 400 A	2400	125	EN 12167		8WC5131		1	1 unit	143	2.240
	• 30 x 5 mm, current intensity 447 A	1100	150	EN 12167		8WC5033-1AA00		1	1 unit	143	2.680
	• 30 x 5 mm, current intensity 447 A	2400	150	EN 12167		8WC5133		1	1 unit	143	2.680
	• 20 x 10 mm, current intensity 520 A	2400	200	EN 12167		8WC5128		1	1 unit	143	3.200
	• 30 x 10 mm, current intensity 630 A	2400	300	EN 12167		8WC5134		1	1 unit	143	5.360
Flat copper profile for ALPHA distribution boards											
	• 12 x 5 mm, current intensity 250 A	250	60	EN 12167		8GK9731-0KK10		1	5 units	039	0.100
		500	60	EN 12167		8GK9731-0KK20		1	5 units	039	0.261
		750	60	EN 12167		8GK9731-0KK30		1	5 units	039	0.500
		1000	60	EN 12167		8GK9731-0KK40		1	5 units	039	0.531
		1250	60	EN 12167		8GK9731-0KK50		1	5 units	039	0.830
	• 20 x 5 mm, current intensity 320 A	250	100	EN 12167		8GK9733-0KK10		1	5 units	039	0.290
		500	60	EN 12167		8GK9733-0KK20		1	5 units	039	0.412
		750	60	EN 12167		8GK9733-0KK30		1	5 units	039	0.850
		1000	60	EN 12167		8GK9733-0KK40		1	5 units	039	1.120
		1250	60	EN 12167		8GK9733-0KK50		1	5 units	039	1.470
	• 30 x 5 mm, current intensity 447 A	250	150	EN 12167		8GK9735-0KK10		1	5 units	039	0.325
		500	150	EN 12167		8GK9735-0KK20		1	5 units	039	0.750
		750	150	EN 12167		8GK9735-0KK30		1	5 units	039	1.460
		1000	150	EN 12167		8GK9735-0KK40		1	5 units	039	2.170
		1250	150	EN 12167		8GK9735-0KK50		1	5 units	039	2.880
	• 30 x 10 mm, current intensity 630 A	250	300	EN 12167		8GK9736-0KK10		1	5 units	039	0.750
		500	300	EN 12167		8GK9736-0KK20		1	5 units	039	1.310
		750	300	EN 12167		8GK9736-0KK30		1	5 units	039	1.972
		1000	300	EN 12167		8GK9736-0KK40		1	5 units	039	3.400
		1250	300	EN 12167		8GK9736-0KK50		1	5 units	039	3.450
① Flat copper profiles, tinned											
	• 12 x 5 mm, current intensity 200 A	2000	60	EN 12167		8WC5051		1	1 unit	143	1.100
	• 15 x 5 mm, current intensity 250 A	2000	75	EN 12167		8WC5052		1	1 unit	143	1.550
	• 20 x 5 mm, current intensity 320 A	2000	100	EN 12167		8WC5053		1	1 unit	143	1.780
	• 25 x 5 mm, current intensity 400 A	2000	125	EN 12167		8WC5054		1	1 unit	143	2.240
	• 30 x 5 mm, current intensity 447 A	2000	150	EN 12167		8WC5055		1	1 unit	143	2.680
	• 20 x 10 mm, current intensity 520 A	2000	200	EN 12167		8WC5063		1	1 unit	143	3.200
	• 30 x 10 mm, current intensity 630 A	2000	300	EN 12167		8WC5065		1	1 unit	143	5.360
	Extension terminals	--	--	--		8JK3201		1	10 sets	046	0.020
	For busbars 12 x 5 mm, tightening torque 6.0 Nm (busbar not included, 1 set = 2 units)										
Busbar connection pieces for bars											
	For flat profiles (max. 630 A)										
	20 mm x 5 mm, 20 mm x 10 mm, 25 mm x 5 mm, 25 mm x 10 mm, 30 mm x 5 mm, 30 mm x 10 mm	40	--	--		8US1921-2BE00		1	6 units	143	0.275
	For flat profiles (max. 630 A)										
	12 mm x 5 mm, 12 mm x 10 mm, 15 mm x 5 mm, 15 mm x 10 mm, 20 mm x 5 mm, 20 mm x 10 mm	55	--	--		8US1921-2BF00		1	12 units	143	0.216

Busbar Systems

8US 60 mm Busbar Systems


Basic assemblies up to 1 600 A

Overview



60 mm busbar system: Basic assembly up to 1 600 A

Selection and ordering data


	Description	Standard	DT	Article No.	Price per PU	PU (UNIT, SET, M)	PS*/P. unit	PG	Weight per PU approx. kg
 8US1943-3AA00  8US1948-2AA00  8US1948-2AA00  8US1941-2BF00	Busbar supports 3-pole, for TT special profiles End and intermediate holder with finger-safe busbar cover (1 pack = 2 busbar supports + finger-safe end covers)	L1-L3	UL 508	8US1943-3AA00		1	1 unit	143	1.140
	Flat copper profiles (approx. 2.4 m long, tinned) TT special profile up to 1 600 A, cross-section 720 mm ²			8US1948-2AA00		1	1 unit	143	15.600
	Cover profiles For flat copper profiles, length 1 000 mm			8US1922-2DA00		1	5 units	143	0.400
	Busbar connection pieces For special profiles/TT profiles up to 1 600 A			8US1941-2BF00		1	3 units	143	1.116
	Partitions, closed 76 mm wide, 2 400 mm long For additional lateral touch protection at the top/bottom			8US1922-1JA00		1	1 unit	143	0.500
 8US1922-1JA00									
 8US1922-2EA0.  8US1922-2EB00	Supports for blanking covers Mounting on busbar, 32 mm depth (2 units per section of blanking cover)	UL 508		8US1922-2EA00		1	4 units	143	0.035
	Mounting on busbar, 107 mm depth (2 units per section of blanking cover)	UL 508		8US1922-2EA01		1	8 units	143	0.081
	Blanking covers Mounting on 8US1922-2EA... support for blanking covers Height 195 mm, Depth 63 mm, Length 700 mm	UL 508		8US1922-2EB00		1	2 units	143	0.700

Busbar Systems

8US 60 mm Busbar Systems

Infeed and connection methods
from 630 A to 1 600 A

Overview



60 mm busbar system: Terminals and covers for infeed and connection methods



Selection and ordering data

	Description	Length mm	Width mm	Max. current A	Conductor cross-sec- tion mm ²	Stan- dard	DT	Article No.	Price per PU	PU (UNIT, SET, M)	PS*/ P. unit	PG	Weight per PU approx. kg
	Infeeds												
	Connecting terminal plate with cover												
	• 3-pole	200	20	80	1.5 ... 16	UL 508		5SH3538		1	5 units	031	0.181
	• 3-pole	200	54	300	6 ... 50	UL 508		8US1921-1BA00		1	1 unit	143	0.446
	• 3-pole	200	81	400	35 ... 120	UL 508		8US1921-1AA00		1	1 unit	143	0.493
8US1921-1AA00													
	Outgoing modules for PE/N												
	Connection module for 4th pole (PE/N) up to 16 mm, must be attached to an adapter/device holder	242	18	--				8US1200-0AA00		1	1 unit	143	0.116
	SR60 connecting terminal plates												
	3-pole with cover, suitable for aluminum conductors (shown without cover)			560	150 ... 300			5SH3535		1	1 unit	031	1.608
5SH3 535													
	Terminal sets												
	3-pole without cover for round cables, suitable for aluminum conductors			560	120 ... 300			8US1941-2AA03		1	1 unit	143	1.577
8US1941-2AA03													

Busbar Systems

8US 60 mm Busbar Systems

Infeed and connection methods
from 630 A to 1 600 A

	Description	Max. current	Conductor cross-sec- tion mm ²	Stan- dard	DT	Article No.	Price per PU	PU (UNIT, SET, M)	PS*/ P. unit	PG	Weight per PU approx. kg
 8US1941-2AA04	Terminal sets 3-pole without cover for flat bars up to 32 x 20 mm	800		UL 508		8US1941-2AA04		1	1 unit	143	1.377
	 8US1922-1GC00 Covers for 8US1941-2AA03/04 terminal set					8US1922-1GC00		1	1 unit	143	0.361
Terminals for circular conductors											
5 mm busbar thickness¹⁾											
 Terminals	12 mm x 5 mm,	180	1.5 ... 16	▶		8US1921-2AA00		100	100 units	143	2.100
	15 mm x 5 mm,	270	4 ... 35	▶		8US1921-2AB00		100	50 units	143	4.700
	20 mm x 5 mm,	400	16 ... 70	▶		8US1921-2AD00		1	50 units	143	0.071
	25 mm x 5 mm,	440	16 ... 120	▶		8US1921-2AC00		1	50 units	143	0.104
	30 mm x 5 mm	180	1.5 ... 16	▶		8US1921-2AA01		1	15 units	143	0.021
		270	4 ... 35	▶		8US1921-2AB01		1	15 units	143	0.045
		400	16 ... 70	▶		8US1921-2AD01		1	15 units	143	0.072
		440	16 ... 120	▶		8US1921-2AC01		1	15 units	143	0.105
10 mm bar thickness											
 Terminals	12 mm x 10 mm, ¹⁾	180	1.5 ... 16	▶		8US1921-2BA00		1	100 units	143	0.023
	15 mm x 10 mm, ¹⁾	270	4 ... 35	▶		8US1921-2BB00		1	50 units	143	0.033
	20 mm x 10 mm,	400	16 ... 70	▶		8US1921-2BD00		1	50 units	143	0.073
	25 mm x 10 mm,	440	16 ... 120	▶		8US1921-2BC00		1	50 units	143	0.102
	30 mm x 10 mm	180	1.5 ... 16	▶		8US1921-2BA01		1	15 units	143	0.022
		270	4 ... 35	▶		8US1921-2BB01		1	15 units	143	0.070
		400	16 ... 70	▶		8US1921-2BD01		1	15 units	143	0.072
		440	16 ... 120	▶		8US1921-2BC01		1	15 units	143	0.107
 8US1941-2AA01	20 mm x 5 mm, 25 mm x 5 mm, 30 mm x 5 mm	500	95 ... 185	▶		8US1941-2AA01		1	6 units	143	0.304
 8US1941-2AA02		600	150 ... 300	▶		8US1941-2AA02		1	3 units	143	0.411

Busbar Systems

8US 60 mm Busbar Systems

Infeed and connection methods
from 630 A to 1 600 A

	Description	Max. current	Conductor cross-sec- tion mm ²	Stan- dard	DT	Article No.	Price per PU	PU (UNIT, SET, M)	PS*/ P. unit	PG	Weight per PU approx. kg
 8US1922-1GA00	Terminal covers for circular conductors (fixing to busbar)										
	For terminals up to 120 mm ² 200 mm long, 84 mm wide				►	8US1922-1GA00		1	10 units	143	0.162
	For terminals up to 300 mm ² 2) 200 mm long, 270 mm wide				►	8US1922-1GA02		1	1 unit	143	0.696
 8US1941-2AC00	Terminals										
	For cable lugs up to 240 mm ² , 630 10 mm bar thickness (threaded bolts M10)					8US1941-2AC00		1	6 units	143	0.356
 8US1941-2BB00	For copper bars or laminated conductors 20 mm x 5 mm, 20 mm x 10 mm, 25 mm x 5 mm, 25 mm x 10 mm, 30 mm x 5 mm, 30 mm x 10 mm	750				8US1941-2BB00		1	6 units	143	0.329
 8US1941-2BA00	For 2 x 40 mm x 10 mm, for TT flat copper profile 30 x 10 profile for flat bars up to 40 x 25	1250				8US1941-2BA00		1	3 units	143	0.815

1) Cannot be used on a special profile up to 1 600 A.


2) Only for 20 mm x 5 mm, 20 mm x 10 mm, 25 mm x 5 mm, 25 mm x 10 mm,
30 mm x 5 mm and 30 mm x 10 mm.

Busbar Systems

8US 60 mm Busbar Systems

Busbar device adapters and device holders
from 630 A to 1 600 A

Overview



60 mm busbar system: Busbar device adapters and device holders

All busbar device adapters and device holders are designed for copper busbars according to DIN 46433, width 12 to 30 mm, thickness 5 mm and 10 mm, and special profiles up to 1 600 A.

Selection and ordering data

For SIRIUS 3RV2/3RT2 load feeders

Welded connecting cable resistant up to 150 °C

	Busbar device adapters for	Number of support rails (35 mm)	Adapter		Connecting cable				Standard	DT	Article No.	Price per PU	PU (UNIT, SET, M)	PS*/P. unit	PG	Weight per PU approx.
			Length	Width	Cross-section	Temperature max.	Rated current	Rated voltage								
			mm	mm	AWG	°C	A	V								kg
	Size S00 devices with screw connection															
	Circuit breakers	1	200	45	12	150	25	690	UL 508	▶	8US1251-5DS10		1	1 unit	143	0.290
	Direct-on-line starters	1	200	45	12	150	25	690	UL 508	▶	8US1251-5DS10		1	1 unit	143	0.290
		1	260	45	12	150	25	690	UL 508	▶	8US1251-5DT10		1	1 unit	143	0.324
	Reversing starters	1	200	45	12	150	25	690	UL 508	▶	8US1251-5DS10		1	1 unit	143	0.290
	+ Device holders	1	200	45	--	--	--	--	UL 508	▶	8US1250-5AS10		1	1 unit	143	0.234
	Size S00 devices with screw connection															
	Circuit breakers	1	200	45	12	150	25	690	UL 508	▶	8US1251-5DS11		1	1 unit	143	0.314
	Circuit breakers	1	260	45	12	150	25	690	UL 508	▶	8US1251-5DT11		1	1 unit	143	0.324
	Direct-on-line starters	1	260	45	12	150	25	690	UL 508	▶	8US1251-5DT11		1	1 unit	143	0.324
	Reversing starters	1	260	45	12	150	25	690	UL 508	▶	8US1251-5DT11		1	1 unit	143	0.324
	+ Device holders	1	260	45	--	--	--	--	UL 508	▶	8US1250-5AT10		1	1 unit	143	0.264

Busbar Systems

8US 60 mm Busbar Systems

Busbar device adapters and device holders from 630 A to 1 600 A

Busbar device adapters for	Number of support rails (35 mm)	Adapter		Connecting cable				Standard	DT	Article No.	Price per PU	PU (UNIT, SET, M)	PS*/P. unit	PG	Weight per PU approx.
		Length	Width	Cross-section	Temperature max.	Rated current	Rated voltage								
		mm	mm	AWG	°C	A	V								kg
Size S0 devices with screw connection															
 Device holders with 3RA2220	Circuit breakers	1	260	45	10	150	32	690	UL 508 ▶	8US1251-5NT10		1	1 unit	143	0.287
	Direct-on-line starters	1	260	45	10	150	32	690	UL 508 ▶	8US1251-5NT10		1	1 unit	143	0.287
	Reversing starters	1	260	45	10	150	32	690	UL 508 ▶	8US1251-5NT10		1	1 unit	143	0.287
	+														
	Device holders	1	260	45	--	--	--	--	UL 508 ▶	8US1250-5AT10		1	1 unit	143	0.264
Size S0 devices with spring-type terminals															
 Device holders with 3RA2220	Circuit breakers	1	260	45	10	150	32	690	UL 508 ▶	8US1251-5NT11		1	1 unit	143	0.345
	Direct-on-line starters	1	260	45	10	150	32	690	UL 508 ▶	8US1251-5NT11		1	1 unit	143	0.345
	Reversing starters	1	260	45	10	150	32	690	UL 508 ▶	8US1251-5NT11		1	1 unit	143	0.345
	+														
	Device holders	1	260	45	--	--	--	--	UL 508 ▶	8US1250-5AT10		1	1 unit	143	0.264

Lateral modules for busbar device adapters

	Description	Length	Width	DT	Article No.	Price per PU	PU (UNIT, SET, M)	PS*/ P. unit	PG	Weight per PU approx.
		mm	mm							kg
	Lateral modules									
	For extending busbar device adapters and device holders of the same length	200	9		8US1998-2BJ10		1	10 units	143	0.021

Busbar Systems

8US 60 mm Busbar Systems

Busbar device adapters and device holders from 630 A to 1 600 A

For SIRIUS 3RV1/3RT1 load feeders

	Busbar device adapters for	Number of support rails (35 mm)	Adapter		Connecting cable				Standard	DT	Article No.	Price per PU	PU (UNIT, SET, M)	PS*/P. unit	PG	Weight per PU approx.
			Length	Width	Cross-section	Temperature max.	Rated current	Rated voltage								
			mm	mm	AWG	°C	A	V								kg
Size S2 devices																
	Circuit breakers	1	182	55	8	105	56	690		►	8US1261-5FM08		1	1 unit	143	0.234
	Contactors + overload relay	1	182	55	8	105	56	690		►	8US1261-5FM08		1	1 unit	143	0.234
	Direct-on-line starters	1	242	55	8	105	56	690		►	8US1261-5FP08		1	1 unit	143	0.293
	Reversing starter adapter +	1	242	55	8	105	56	690		►	8US1261-5FP08		1	1 unit	143	0.293
	Device holders ¹⁾	--	242	54	--	--	--	--	--	►	8US1260-5AP00		1	1 unit	143	0.182
	+ Connecting wedges (2 units needed for attachment)	--	--	--	--	--	--	--	--	►	8US1998-1AA00		100	100 units	143	0.052
Size S3 devices with screw connection																
	Circuit breakers	--	215	72	4	105	80	600	UR, CSA		8US1211-4TR00		1	1 unit	143	0.623

¹⁾ Spacer and fixing screw for reversing contactor are included in the scope of delivery.

Busbar Systems

8US 60 mm Busbar Systems

Busbar device adapters and device holders
from 630 A to 1 600 A

For motor starter protectors/circuit breakers and switch disconnectors which require busbar device adapters for mounting on busbars

	Busbar device adapters for	Adapter		Connecting cable			Standard	DT	Article No.	Price per PU	PU (UNIT, SET, M)	PS*/P. unit	PG	Weight per PU approx.
		Length	Width	Type	Rated current	Rated voltage								
		mm	mm		A	V								kg
	3VL molded case circuit breakers¹⁾													
	3VL1 ²⁾	175	108	Busbars	160	690			8US1211-4SL01		1	1 unit	143	0.579
	3VL2 ²⁾	175	108	Busbars	160	690			8US1211-4SL01		1	1 unit	143	0.579
	3VL3 ³⁾	175	108	Busbars	250	690			8US1211-4SL00		1	1 unit	143	0.641
	3VL1 to 3VL4 and also with RCD module ²⁾ see chapter 2	320	184	M10 pin connector	400	690			8US1210-4AF00 +		1	1 unit	143	2.688
	3VL5	325	184	Tubular contacts	580	690			8US1213-4AF00		1	1 unit	143	3.239
	3VL UL circuit breakers													
	VL150X UL CG frame	190	105	Tubular contacts	150	600	UL 508		8US1213-4AQ01		1	1 unit	143	1.116
	VL150 UL DG frame	190	105	Tubular contacts	150	600	UL 508		8US1213-4AQ03		1	1 unit	143	1.114
	VL250 UL FG frame	190	105	Tubular contacts	250	600	UL 508		8US1213-4AQ03		1	1 unit	143	1.114
	VL400 UL JG-Frame	296	140	Tubular contacts	400	600	UL 508		8US1213-4AH00		1	1 unit	143	2.539
	VL400X UL LG-Frame	296	140	Tubular contacts	540	600	UL 508		8US1213-4AH00		1	1 unit	143	2.539
	3KA and 3KL switch disconnectors													
	3KA52 ⁴⁾ 3KA53 ⁴⁾ 3KL52 ⁴⁾ 3KL53 ⁴⁾	320	184	M10 pin connector	630	690			8US1210-4AF00		1	1 unit	143	2.688
	3KA55 ⁴⁾ 3KA57 ⁴⁾ 3KA58 ⁴⁾ 3KL55 ⁴⁾ 3KL57 ⁴⁾	320	250	M10 pin connector	630	690			8US1210-4AG00		1	1 unit	143	2.926
	3NP5 fuse switch disconnectors													
	3NP50 60 (NH00)	175	108	Busbars	160	690			8US1291-4SB00		1	1 unit	143	0.522
	3NP52 3NP53 3NP54 ⁵⁾	320	250	M10 pin connector	630	690	UL 508		8US1210-4AG00		1	1 unit	143	2.926

¹⁾ Observe the short-circuit strength of the busbar system. Short-circuit strength > 50 kA on request.

²⁾ Usable only for 3VL circuit breakers with line-side box terminals.

³⁾ Only for 3VL 250 A circuit breakers, for screw fixing with metric thread, for flat terminals.

⁴⁾ Without connecting cables. The connecting cable between adapter and device should be manufactured in accordance with the rated current as a round cable, e.g. H07V-R with cable lug, or as a flat conductor for an M10 stud terminal.

⁵⁾ Without connecting cables. The connecting cable between adapter and device should be manufactured in accordance with the rated current as a round cable, e.g. H07V-R, bared at both ends for tunnel terminals.

Busbar Systems

8US 60 mm Busbar Systems

Busbar device adapters and device holders from 630 A to 1 600 A

For SIRIUS 3RA6 compact starters according to IEC and UL

Welded connecting cable resistant up to 105 °C

	Busbar device adapter for	Number of support rails (35 mm)	Adapter		Connecting cable				Standard	DT	Article No.	Price per PU	PU (UNIT, SET, M)	PS*/P. unit	PG	Weight per PU approx.
			Length	Width	Cross-section	Temperature max.	Rated current	Rated voltage								
			mm	mm	AWG	°C	A	V								kg
 Device holders	Size equivalent to 3RA61															
	Direct-on-line starters	1	200	45	10	105	32	690	UR, CSA	►	8US1211-1NS10		1	1 unit	143	0.300
 Device holders	Size equivalent to 3RA62															
	Reversing starters	1	200	45	10	105	32	690	UR, CSA	►	8US1211-1NS10		1	1 unit	143	0.300
	+ Device holders	1	200	45	--	--	--	--	UL 508	►	8US1250-1AA10		1	1 unit	143	0.278

Device holders

Device holders

Busbar Systems

8US 60 mm Busbar Systems

Busbar device adapters and device holders
from 630 A to 1 600 A

For universal device design

	Number of support rails (35 mm)	Adapter		Connecting cable				Standard	DT	Article No.	Price per PU	PU (UNIT, SET, M)	PS*/P. unit	PG	Weight per PU approx.
		Length	Width	Cross-section	Temperature max.	Length	Rated current	Rated voltage							
		mm	mm	AWG	°C	mm	A	V							kg
Devices 45 mm wide															
Device holder for side mounting onto busbar device adapter, no electrical contact															
	1	200	45	--	--	--	--	--	UL 508 ▶	8US1250-1AA10		1	1 unit	143	0.278
8US1250-1AA10	1	200	45	--	--	--	--	--	UL 508 ▶	8US1250-5AS10		1	1 unit	143	0.234
	1	260	45	--	--	--	--	--	UL 508 ▶	8US1250-5AT10		1	1 unit	143	0.264
8US1250-5AT10	1	260	45	--	--	--	--	--	UL 508 ▶	8US1250-5AT10		1	1 unit	143	0.264
	1	260	45	--	--	--	--	--	UL 508 ▶	8US1250-5AT10		1	1 unit	143	0.264
8US1250-5AT10	1	260	45	--	--	--	--	--	UL 508 ▶	8US1250-5AT10		1	1 unit	143	0.264
Devices 45 mm and 72 mm wide															
Busbar device adapter with connecting cables for contact with busbars, welded connecting cable resistant up to 150 °C															
	1	200	45	12	150	165	25	690	UL 508 ▶	8US1251-5DS11		1	1 unit	143	0.314
8US1251-5DS10	1	200	45	12	150	99	25	690	UL 508 ▶	8US1251-5DS10		1	1 unit	143	0.290
	1	260	45	12	150	99	25	690	▶	8US1251-5DT10		1	1 unit	143	0.324
8US1211-4TR00	1	260	45	12	150	165	25	690	UL 508 ▶	8US1251-5DT11		1	1 unit	143	0.324
	1	260	45	10	150	99	32	690	UL 508 ▶	8US1251-5NT10		1	1 unit	143	0.287
8US1251-5NT10	1	260	45	10	150	165	32	690	UL 508 ▶	8US1251-5NT11		1	1 unit	143	0.345
	1	200	45	10	105	118	32	690	UL 508 ▶	8US1211-1NS10		1	1 unit	143	0.300
8US1211-1NS10	--	215	72	4	105	210	100	690	UR, CSA	8US1211-4TR00		1	1 unit	143	0.623
8US1211-4TR00	--	215	72	4	105	210	100	690	UR, CSA	8US1211-4TR00		1	1 unit	143	0.623
Lateral modules															
For extending busbar device adapters and device holders of the same length															
8US1998-2BJ10	--	200	9	--	--	--	--	--		8US1998-2BJ10		1	10 units	143	0.021
8US1998-2BJ10	--	200	9	--	--	--	--	--		8US1998-2BJ10		1	10 units	143	0.021

Busbar Systems

8US 60 mm Busbar Systems



Accessories for SIRIUS 3RV2/3RT2 load feeders

Selection and ordering data

Accessories for SIRIUS 3RV2/3RT2 load feeders are designed for:

- 8US 60 mm busbar system for Cu busbars according to DIN 46433

- Width 12 mm up to 30 mm, thickness 5 mm and 10 mm
- And special profiles up to 1 600 A

	Description	Length mm	Width mm	DT	Article No.	Price per PU	PU (UNIT, SET, M)	PS*/ P. unit	PG	Weight per PU approx. kg
Busbar connection pieces for bars										
	20 mm × 5 mm, 20 mm × 10 mm, 25 mm × 5 mm, 25 mm × 10 mm, 30 mm × 5 mm, 30 mm × 10 mm	40			8US1921-2BE00		1	6 units	143	0.275
	12 mm × 5 mm, 12 mm × 10 mm, 15 mm × 5 mm, 15 mm × 10 mm, 20 mm × 5 mm, 20 mm × 10 mm	55			8US1921-2BF00		1	12 units	143	0.216
Support rails (35 mm)										
	Support rails made of plastic with fixing screws		45		8US1998-7CB45		1	10 units	143	0.014
	Support rails made of plastic with fixing screws		54		8US1998-7CB54		1	10 units	143	0.016
	Support rails made of plastic with fixing screws		72		8US1998-7CB72		1	10 units	143	0.030
Connecting elements										
	For connecting busbar adapters and device holders			▶	8US1998-1AA10		1	50 units	143	0.001
Spacers										
	Fix the feeder to the busbar adapter			▶	8US1998-1BA10		1	10 units	143	0.005
Vibration & shock kit										
Lateral modules										
	For extending busbar device adapters and device holders of the same length	200	9		8US1998-2BJ10		1	10 units	143	0.021

Busbar Systems

8US 60 mm Busbar Systems

Connector for 3NP1 fuse switch disconnectors

Selection and ordering data

For snap connections to 60 mm busbar systems

	Rated current I_u	LV HRC fuse links according to IEC 60269-1	DT	Article No.	Price per PU	PU (UNIT, SET, M)	PS*/P. unit	PG	Weight per PU approx. kg
	A	Size							
For cover level 32 / 70 mm, with reach-around protection for 8US busbar system									
	Basic units								
	Flat terminals								
	160	00 / 000		3NP1133-1BC10		1	1 unit	143	1.155
	250	1 and 0		3NP1143-1BC10		1	1 unit	143	3.245
	400	2 and 1		3NP1153-1BC10		1	1 unit	143	4.314
	630	3 and 2		3NP1163-1BC10		1	1 unit	143	5.260
	Box terminals								
	160	000		3NP1123-1BC20		1	1 unit	143	0.971
	160	00 / 000		3NP1133-1BC20		1	1 unit	143	1.146
	250	1 and 0		3NP1143-1BC20		1	1 unit	143	3.306
	400	2 and 1		3NP1153-1BC20		1	1 unit	143	4.672
	630	3 and 2		3NP1163-1BC20		1	1 unit	143	5.538
	With MFM electromechanical fuse monitoring								
	Flat terminals								
	160	00 / 000		3NP1133-1BC11		1	1 unit	143	1.698
	250	1 and 0		3NP1143-1BC11		1	1 unit	143	3.914
	400	2 and 1		3NP1153-1BC11		1	1 unit	143	5.016
	630	3 and 2		3NP1163-1BC11		1	1 unit	143	5.910
	Box terminals								
	160	00 / 000		3NP1133-1BC21		1	1 unit	143	1.702
	250	1 and 0		3NP1143-1BC21		1	1 unit	143	3.993
	400	2 and 1		3NP1153-1BC21		1	1 unit	143	5.500
	630	3 and 2		3NP1163-1BC21		1	1 unit	143	6.223
	With EFM 10 electronic fuse monitoring								
	Flat terminals								
	160	00 / 000		3NP1133-1BC12		1	1 unit	143	1.394
	250	1 and 0		3NP1143-1BC12		1	1 unit	143	3.564
	400	2 and 1		3NP1153-1BC12		1	1 unit	143	4.666
	630	3 and 2		3NP1163-1BC12		1	1 unit	143	5.555
	Box terminals								
	160	000		3NP1123-1BC22		1	1 unit	143	1.109
	160	00 / 000		3NP1133-1BC22		1	1 unit	143	1.406
	250	1 and 0		3NP1143-1BC22		1	1 unit	143	3.650
	400	2 and 1		3NP1153-1BC22		1	1 unit	143	5.014
	630	3 and 2		3NP1163-1BC22		1	1 unit	143	5.826
	With EFM 20 electronic fuse monitoring and line monitoring								
	Flat terminals								
	160	00 / 000		3NP1133-1BC13		1	1 unit	143	1.411
	250	1 and 0		3NP1143-1BC13		1	1 unit	143	3.641
	400	2 and 1		3NP1153-1BC13		1	1 unit	143	4.750
	630	3 and 2		3NP1163-1BC13		1	1 unit	143	5.611
	Box terminals								
	160	000		3NP1123-1BC23		1	1 unit	143	1.121
	160	00 / 000		3NP1133-1BC23		1	1 unit	143	1.470
	250	1 and 0		3NP1143-1BC23		1	1 unit	143	3.685
	400	2 and 1		3NP1153-1BC23		1	1 unit	143	5.090
	630	3 and 2		3NP1163-1BC23		1	1 unit	143	5.920
	Accessories								
	Connection modules								
	For 32-mm cover level with box terminal 6 mm ... 70 mm ²			3NP1933-1BC00		1	1 unit	143	0.193

* You can order this quantity or a multiple thereof.

Busbar Systems

8US 60 mm Busbar Systems

UL applications

Overview

Short-circuit strength

The short-circuit strength of the busbar system is dependent on the distance of the busbar supports and on the busbar cross-section.

The short-circuit strength of the whole system is dependent on the short-circuit strength of the busbars and of the adapters with circuit breakers or switch disconnectors. If one of these values is lower than the prospective short-circuit current at the installation site, a current-limiting protective device has to be mounted upstream of the 8US busbar system. This may also be mounted as a feeder circuit breaker on the busbar system itself. The table below provides a selection aid for this purpose.

Selection aid for UL applications

Components used		Short-circuit current rating (SCCR) Total kA	Ambient conditions					Max. spacing of busbar supports mm
Article No.	Description		Max. rated current I_e A	Rated voltage U_e V	Busbar dimensions	Rated current of the fuse used I_e A	Fuse type used	
8US1921-1AA00	Connection terminal plate with cover, conductor cross-section 35 ... 120 mm ²	10	--	600	--	--	--	533
8US1921-1AA00		65	400	480	--	400	3VL-UL; 3RV.7; 3RV.8	800
8US1921-1AA00		50	600	480	--	600	3VL-UL; 3RV.7; 3RV.8	800
8US1921-1AA00		35	400	600	--	400	3VL-UL; 3RV.7; 3RV.8	800
8US1921-1AA00		35	600	600	--	600	3VL-UL; 3RV.7; 3RV.8	800
8US1921-1AA00		100	600	480	--	600	J or T	800
8US1921-1AA00		100	500	600	--	500	J or T	800
8US1921-1AA00		100	400	480	--	400	RK1	800
8US1921-1AA00		100	400	600	--	400	RK1	800
8US1922-2AA00	Cover profiles for busbars	--	--	--	--	--	--	--
8US1922-2BA00	Cover profiles for busbars	--	--	--	--	--	--	--
8US1922-2DA00	Cover profiles for flat copper profile	--	--	--	--	--	--	--
8US1923-3UA01	End and intermediate holders for flat copper profiles	18	150	600	12x5	--	--	250
8US1923-3UA01		18	150	600	12x5	--	--	400
8US1923-3UA01		65	150	480	12x5	250	3VL-UL; 3RV.7; 3RV.8	800
8US1923-3UA01		25	150	600	12x5	250	3VL-UL; 3RV.7; 3RV.8	800
8US1923-3UA01		100	150	480	12x5	400	RK1, J or T	800
8US1923-3UA01		100	150	600	12x5	175	J or T	800
8US1923-3UA01		100	150	600	12x5	100	RK1	800
8US1923-3UA01		18	150	600	12x10	--	-	250
8US1923-3UA01		18	150	600	12x10	--	-	400
8US1923-3UA01		65	150	480	12x10	250	3VL-UL; 3RV.7; 3RV.8	800
8US1923-3UA01		25	150	600	12x10	250	3VL-UL; 3RV.7; 3RV.8	800
8US1923-3UA01		100	150	480	12x10	400	RK1, J or T	800
8US1923-3UA01		100	150	600	12x10	175	J or T	800
8US1923-3UA01		100	150	600	12x10	100	RK1	800
8US1923-3UA01		18	362	600	20x5	--	-	250
8US1923-3UA01		18	362	600	20x5	--	-	400
8US1923-3UA01		65	362	480	20x5	400	3VL-UL; 3RV.7; 3RV.8	800
8US1923-3UA01		35	362	600	20x5	400	3VL-UL; 3RV.7; 3RV.8	800
8US1923-3UA01		100	362	480	20x5	500	J or T	800
8US1923-3UA01		100	362	600	20x5	400	J or T	800
8US1923-3UA01		100	362	480	20x5	400	RK1	800
8US1923-3UA01		100	362	600	20x5	200	RK1	800
8US1923-3UA01		18	564	600	20x10	--	-	250
8US1923-3UA01		18	564	600	20x10	--	-	400
8US1923-3UA01		65	564	480	20x10	400	3VL-UL; 3RV.7; 3RV.8	800
8US1923-3UA01		35	564	600	20x10	400	3VL-UL; 3RV.7; 3RV.8	800
8US1923-3UA01		100	564	480	20x10	500	J or T	800
8US1923-3UA01		100	564	600	20x10	400	J or T	800
8US1923-3UA01		100	564	480	20x10	400	RK1	800
8US1923-3UA01		100	564	600	20x10	200	RK1	800
8US1923-3UA01		25	500	600	30x5	--	-	250
8US1923-3UA01	22	500	600	30x5	--	-	400	
8US1923-3UA01	65	500	480	30x5	400	3VL-UL; 3RV.7; 3RV.8	800	
8US1923-3UA01	35	500	600	30x5	600	3VL-UL; 3RV.7; 3RV.8	800	

Busbar Systems

8US 60 mm Busbar Systems

UL applications

Components used		Short-circuit current rating (SCCR) Total kA	Ambient conditions					
Article No.	Description		Max. rated current I_e	Rated voltage U_e	Busbar dimensions	Rated current of the fuse used I_e	Fuse type used	Max. spacing of busbar supports
			A	V		A		mm
8US1923-3UA01	End and intermediate holders for flat copper profiles	100	500	480	30x5	500	J or T	800
8US1923-3UA01		100	500	600	30x5	500	J or T	800
8US1923-3UA01		100	500	480	30x5	400	RK1	800
8US1923-3UA01		100	500	600	30x5	400	RK1	800
8US1923-3UA01		25	756	600	30x10	--	--	250
8US1923-3UA01		22	756	600	30x10	--	--	400
8US1923-3UA01		65	756	480	30x10	400	3VL-UL; 3RV.7; 3RV.8	800
8US1923-3UA01		35	756	600	30x10	400	3VL-UL; 3RV.7; 3RV.8	800
8US1923-3UA01		50	756	480	30x10	600	3VL-UL; 3RV.7; 3RV.8	800
8US1923-3UA01		25	756	600	30x10	600	3VL-UL; 3RV.7; 3RV.8	800
8US1923-3UA01		100	756	480	30x10	600	J or T	800
8US1923-3UA01		100	756	600	30x10	450	J or T	800
8US1923-3UA01		100	756	480	30x10	400	RK1	800
8US1923-3UA01		100	756	600	30x10	400	RK1	800
8US1923-3UA01		65	--	480	--	400	3VL-UL; 3RV.7; 3RV.8	800
8US1923-3UA01		50	--	480	--	600	3VL-UL; 3RV.7; 3RV.8	800
8US1923-3UA01		35	--	600	--	600	3VL-UL; 3RV.7; 3RV.8	800
8US1923-3UA01		100	--	480	--	600	J or T	800
8US1923-3UA01		100	--	600	--	500	J or T	800
8US1923-3UA01		100	--	480	--	400	RK1	800
8US1923-3UA01		100	--	600	--	400	RK1	800
8US1213-4AH00	Device adapters for 3VL UL molded-case circuit breakers	65	630	480	--	600	--	400
8US1213-4AH00		50	630	600	--	600	--	400
8US1213-4AH00		65	630	480	--	400	3VL-UL; 3RV.7; 3RV.8	800
8US1213-4AH00		35	630	600	--	400	3VL-UL; 3RV.7; 3RV.8	800
8US1213-4AH00		50	630	480	--	600	3VL-UL; 3RV.7; 3RV.8	800
8US1213-4AH00		25	630	600	--	600	3VL-UL; 3RV.7; 3RV.8	800
8US1211-4TR00	Busbar adapter 45 mm/ 72 mm	10	80	600	--	--	--	400
8US1213-4AQ01	Busbar adapters for 3VL UL molded-case circuit breakers	65	250	480	--	250	--	400
8US1213-4AQ01		50	250	600	--	250	--	400
8US1213-4AQ01		65	250	480	--	250	3VL-UL; 3RV.7; 3RV.8	800
8US1213-4AQ01		25	250	600	--	250	3VL-UL; 3RV.7; 3RV.8	800
8US1948-2AA00	Flat copper profiles	103	1400	600	--	1600	Class L	N/A
8US1943-3AA00	Busbar supports, 3-pole, double-T profile	30	1200	600	--	--	--	400
8US1943-3AA00		25	1200	600	--	--	--	700
8US1943-3AA00		65	1200	480	--	800	3VL-UL; 3RV.7; 3RV.8	800
8US1943-3AA00		30	1200	600	--	800	3VL-UL; 3RV.7; 3RV.8	800
8US1943-3AA00		100	1200	480	--	800	Class T	800
8US1943-3AA00		100	1200	600	--	600	J or T	800
8US1943-3AA00		100	1200	480	--	600	Class RK1	800
8US1943-3AA00		100	1200	600	--	400	Class RK1	800
8US1943-3AA00		30	1400	600	--	--	--	400
8US1943-3AA00		25	1400	600	--	--	--	700
8US1943-3AA00		65	1400	480	--	800	3VL-UL; 3RV.7; 3RV.8	800
8US1943-3AA00		30	1400	600	--	800	3VL-UL; 3RV.7; 3RV.8	800
8US1943-3AA00		100	1400	480	--	800	T	800
8US1943-3AA00		100	1400	600	--	600	J or T	800
8US1943-3AA00		100	1400	480	--	600	RK1	800
8US1943-3AA00		100	1400	600	--	400	RK1	800
8US1943-3AA00		65	--	480	--	800	3VL-UL; 3RV.7; 3RV.8	800
8US1943-3AA00		30	--	600	--	800	3VL-UL; 3RV.7; 3RV.8	800
8US1943-3AA00		100	--	480	--	800	T	800
8US1943-3AA00		100	--	600	--	600	J or T	800
8US1943-3AA00		100	--	480	--	600	RK1	800
8US1943-3AA00		100	--	600	--	400	RK1	800
8US1922-1GC00	Covers for connection terminal set	--	--	--	--	--	--	--

Busbar Systems

8US 60 mm Busbar Systems

UL applications

Components used		Short-circuit current rating (SCCR) Total	Ambient conditions					
Article No.	Description		Max. rated current I_e	Rated voltage U_e	Busbar dimensions	Rated current of the fuse used I_e	Fuse type used	Max. spacing of busbar supports
			kA	A	V		A	
8US1941-2AA03	Connection terminals, 3-pole	65	400	480	--	400	3VL-UL; 3RV.7; 3RV.8	800
8US1941-2AA03		35	400	600	--	400	3VL-UL; 3RV.7; 3RV.8	800
8US1941-2AA03		100	500	480	--	500	J or T	800
8US1941-2AA03		100	300	600	--	300	J or T	800
8US1941-2AA03		100	400	480	--	400	RK1	800
8US1941-2AA03		100	200	600	--	200	RK1	800
8US1211-1NS10 / 8US1251-5DS10 / 8US1251-5DT11 / 8US1251-5DT10	Busbar device adapters and device holders	5	32	600	--	12.5	3RV20 + 3RV2928-1K	400
8US1211-1NS10 / 8US1251-5DS10 / 8US1251-5DT11 / 8US1251-5DT10	Busbar device adapters and device holders	5	32	480	--	32	3RV20 + 3RV2928-1K	400
8US1211-1NS10 / 8US1251-5DS10 / 8US1251-5DT11 / 8US1251-5DT10	Busbar device adapters and device holders	30	32	600	--	12.5	3RV20 + 3RV2928-1K	400
8US1211-1NS10 / 8US1251-5DS10 / 8US1251-5DT11 / 8US1251-5DT10	Busbar device adapters and device holders	65	32	480	--	16	3RV20	400
8US1211-1NS10 / 8US1251-5DS10 / 8US1251-5DT11 / 8US1251-5DT10	Busbar device adapters and device holders	65	32	600	--	25	3RV20 + 3RV2928-1K	400
8US1211-1NS10 / 8US1251-5DS10 / 8US1251-5DT11 / 8US1251-5DT10	Busbar device adapters and device holders	50	32	480	--	32	3RV20 + 3RV2928-1K	400
8US1211-1NS10 / 8US1251-5DS10 / 8US1251-5DT11 / 8US1251-5DT10	Busbar device adapters and device holders	5	25	600	--	--	--	400
8US1211-1NS10 / 8US1251-5DS10 / 8US1251-5DT11 / 8US1251-5DT10	Busbar device adapters and device holders	5	32	600	--	--	--	400
8US1211-1NS10 / 8US1251-5DS10 / 8US1251-5DT11 / 8US1251-5DT10	Busbar device adapters and device holders	5	25	600	--	--	--	400
8US1211-1NS10 / 8US1251-5DS10 / 8US1251-5DT11 / 8US1251-5DT10	Busbar device adapters and device holders	5	32	600	--	--	--	400
8US1211-1NS10 / 8US1251-5DS10 / 8US1251-5DT11 / 8US1251-5DT10	Busbar device adapters and device holders	5	25	600	--	--	--	400
8US1211-1NS10 / 8US1251-5DS10 / 8US1251-5DT11 / 8US1251-5DT10	Busbar device adapters and device holders	5	32	600	--	--	--	400
8US1251-5NT10	Busbar adapters for devices of size S0	5	30	600	--	--	--	400
8US1250-1AA10	Device holders for SIRUS 3RA6	--	--	--	--	--	--	--
8US1250-5AT10	Device holders for devices of width 45 mm	--	--	--	--	--	--	--
8US1250-5AS10		--	--	--	--	--	--	--

Selection and ordering data

Accessories are designed for:

- 8US 60 mm busbar system for Cu busbars according to DIN 46433
- Width 12 mm up to 30 mm, thickness 5 mm and 10 mm
- And special profiles up to 1 600 A

Adapters and device holders for SIRIUS 3RV1/3RT1 load feeders (discontinued types)


	Busbar device adapters	Number of support rails (35 mm)	Adapter Length	Width	Connecting cable			DT	Article No.	Price per PU	PU (UNIT, SET, M)	PS*/P. unit	PG	Weight per PU approx.
					Cross-section	Rated current	Rated voltage							
			mm	mm	mm ²	A	V							kg
 8US12 50-5RM07	Busbar device adapters with terminals (at top) for any arrangement of components													
	--	1	182	45	1.5 ... 4	25	690		8US1250-5RM07		1	1 unit	143	0.157
	Device holders for lateral mounting to busbar device adapters of the same length													
	Device holders	1	182	45	--	--	--	▶	8US1250-5AM00		1	1 unit	143	0.138
	Device holders	1	182	55	--	--	--	▶	8US1260-5AM00		1	1 unit	143	0.180
 8US1950-1AM00	Device holders	--	242	54	--	--	--	▶	8US1260-5AP00		1	1 unit	143	0.182
	Connecting wedges (2 units needed for attachment)	--	--	--	--	--	--	▶	8US1998-1AA00		100	100 units	143	0.052
	Lateral modules for extending busbar device adapters and device holders of the same length													
 8US1998-2BM00	Lateral modules	--	182	13.5	--	--	--		8US1998-2BM00		1	4 units	143	0.032

Busbar Systems

8US 60 mm Busbar Systems

Accessories

Other accessories for SIRIUS 3RV1/3RT1 load feeders (discontinued types)

	Description	Length	Width	DT	Article No.	Price per PU	PU (UNIT, SET, M)	PS*/P. unit	PG	Weight per PU approx. kg
		mm	mm							
  Support rails	Support rails (35 mm) - plastic with fixing screws		45		8US1998-7CA15		1	10 units	143	0.010
			55		8US1998-7CA16		1	10 units	143	0.001
			72		8US1998-4AA00		1	10 units	143	0.014
			90		8US1998-7CA08		1	10 units	143	0.020
			110		8US1998-7CA10		1	10 units	143	0.019
 NSE0_00347 8US1998-1DA00	Connection holders For fixing the circuit breaker to the support rail (for SIRIUS size S00/S0)				8US1998-1DA00		100	20 units	143	0.100
 8US1998-1CA00	Screw holders For supplementary screw mounting of the branch (for SIRIUS size S00/S0)				8US1998-1CA00		100	20 units	143	0.200
 8US1998-1BA00	Spacers Fix the feeder to the busbar adapter (for SIRIUS size S00/S0)			▶	8US1998-1BA00		100	100 units	143	0.100
 Connecting wedges	Connecting wedges For mechanical linking of busbar device adapters and device holder (2 units per combination)			▶	8US1998-1AA00		100	100 units	143	0.052

Overview

Material properties

Busbar supports and busbar-mounting fuse bases (see "Built-in components" from page 10/33) are manufactured from glass-fiber reinforced, thermoplastic polyester (color RAL 7035, light gray). The material ensures excellent mechanical, chemical and electrical properties. Furthermore, the material has an extremely low flammability and meets the requirements of UL 94 V0. This satisfies the load requirements of the busbar supports at rated operational voltage 500 V and rated currents at 200 A to 630 A, as well as the rated short-circuit strength 50 kA.

Continuous currents depending on the Cu power rail dimensions and Cu busbar temperatures at 35 °C ambient temperature

Cu busbar dimensions H × D mm × mm	Continuous current for open busbar run - ambient temperature 35 °C A	Continuous current of fuse link Operational class gL/gG A
12 × 5	200	200
12 × 10	360	315
15 × 5	250	250
15 × 10	447	400
20 × 5	320	315
20 × 10	520	500
25 × 5	400	400
25 × 10	580	500
30 × 5	447	400
30 × 10	630	630

As far as other types of upstream protective devices are concerned, please observe the permissible continuous current of the busbar.

Dynamic rated short-circuit strength

The electrodynamic load of the busbars depends on the level of short-circuit current, the length of the busbar section through which the current flows, the support spacing of the busbar supports and, of course, on the distance between the busbars themselves. This is because, for example, if an LV HRC fuse is connected upstream to the busbars in the protective device, the let-through current i_D is the maximum current to flow through this protective device. The value i_D depends on the maximum system short-circuit current and the current-limiting action of the protective device used. The permissible let-through values of the protective devices are specified by the manufacturers in the form of a current limitation diagram as a function of the so-called prospective short-circuit current (r.m.s. value of the possible rated short-circuit current for the system).

The current-limiting characteristics for the fuse links can be found in the Technical Information, see note on Technical Information at the beginning of the chapter.

For busbar supports with busbars of 12 mm x 5 mm to 20 mm x 5 mm, the distance between the holders of the support spacing should be adapted to suit the bars in the distribution board and, if possible, should not exceed 250 mm. When using busbars of 25 mm x 5 mm, 30 mm x 5 mm, 12 mm x 10 mm to 30 mm x 10 mm the distance can also be up to 500 mm. In the case of larger distances, subcarriers must be fitted, as increased support spacing reduces the dynamic stability.


It is essential to ensure that the permissible current carrying capacity of the individual busbars is not exceeded. A center infeed is required in the limit range. However, the infeed can also be carried out at both ends of the busbar.

Ambient temperatures

When dimensioning the busbars based on rated currents, the ambient temperature and the Cu busbar temperature must also be taken into account.

The location of the busbar system and its ability to dissipate heat through convection also play a key role in this calculation. Because conditions can vary for each distribution board, the values in the following table serve as a guideline only. However, they must be applied to the entire busbar length.

Diagram of the dynamic short-circuit strength of the busbars



i_D : Let-through values (kA) of the LV HRC fuse links, operational class gL/gG with rated current 200 A to 630 A for a prospective short-circuit current $I_p = 120$ kA.

Distribution board components

Planning dimensions


	Width mm	MW
NEOZED bus-mounting bases D02		
Covers	27	1.5
Covers, extra wide	36	2.0
Covers, double width	54	3.0
DIAZED bus-mounting bases DII		
Covers	42	2.3
Covers, double width	84	4.7
DIAZED bus-mounting bases DIII		
Covers	57	3.2
Covers, double width	114	6.3
NEOZED bus-mounting switch disconnectors	27	1.5
LV HRC fuse switch disconnectors size 00	108	6

Number of built-in components that can be mounted

Height	Width	Cutout width	D02/63 A 5SH5241	D02/63 A 5SH5242	D02/63 A 5SH5243	DII/25 A 5SH2042	DIII/63 A 5SH2242	5SG7230 bus- mounting switch disconnectors D02 (26.8 mm width)
mm	mm	mm	(27 mm width)	(36 mm width)	(54 mm width)	(42 mm width)	(57 mm width)	
300	250	216	8	6	4	5	3	8
	500	466	17	12	8	11	8	17
	750	716	26	19	13	17	12	26
450	250	216	8	6	4	5	3	8
	500	466	17	12	8	11	8	17
	750	715	26	19	13	17	12	26


Dimensional drawings

8GK9 busbar support




8GK9711-0KK03

N/PE busbar support




5SH3540

Connection modules




5SH5538


Connection modules

8US1921-1AA00
shown closed

Connection modules

8US1921-1AA00
shown open

Connection modules



8US1921-1BA00

Overview

Rail-adaptable built-in components, such as NEOZED and DIAZED bus-mounting bases, adapters for modular installation devices, fuse switch disconnectors and NEOZED bus-mounting fuse switch disconnectors are made of glass-fiber reinforced, thermoplastic polyester. The material ensures the required mechanical, chemical and electrical properties.

Efficient power distribution up to 630 A. Users have several options for mounting the SR60 busbar system:

1. Mounting in distribution boards

The busbar supports are mounted on the longitudinal stays. Once the built-in components are mounted and connected, the touch protection cover (section cover) protects against accidental contact with live parts.

2. Installation in industrial control cabinets

The demand for comprehensive touch protection has generated new solutions: built-in components, such as busbar fuse bases

have integrated reach-through guards, enable the implementation of cost-effective overall solutions.


Previously two optional solutions were provided, which can now be replaced using new technology: touch protection over base and edges or touch protection over partitions.

Higher overall efficiency and cost savings in the plant engineering industry.

The fuse holders for cylindrical fuses, size 10 x 38 and for American fuses, Class CC, can be used in the international plant engineering industry. In addition, Siemens offers a broad range of UL-approved components for the design of switchgear assembly according to UL 508 A.

For further information, see chapter "BETA Devices according to UL Standards" in Catalog LV 16 · 2009.

Fuse holders are available with a connection module 16 mm² and screwless terminals; this offers users maximum safety and comfort.



Benefits

- The direct contact of the rail-adaptable switching and installation devices on the Cu busbars reduces distribution panels and mounting times
- Compared to conventional installation, the transfer resistance of the connections is drastically reduced. This prevents unnecessary temperature rise.
- New built-in components with touch protection ensure comprehensive touch protection without the previously required partitions.
- International application due to UL-approved components.
- Enhanced effectiveness and increased safety due to screwless terminals.

Built-in components

Technical specifications

		NEOZED SR60 bus-mounting bases		DIAZED SR60 bus-mounting bases	
		5SG6202 5SG6206 5SG6207 D01	D02	5SF6014 5SF6015 5SF6020 DII	5SF6214 5SF6215 5SF6220 DIII
Standards		IEC 60269-3, DIN VDE 0636-3			
Rated voltage	V AC/DC	400/250		500	690/600
Rated frequency	Hz	50			
Rated current	A	16 (with NEOZED retain- ing springs)	63	25	63
Rated conditional short-circuit current	kA AC kA DC	50 8		50 8	
For fuse links with power losses per phase	W	2.5	5.5	4	7
Busbar center-to-center spacing	mm	60		60	

		3NW7431	3NW7431-OHG
Standards		IEC 60269-2, UL 512, CSA C22.2	UL 512, CSA C22.2
Approvals		UL, CSA	UL, CSA
Size		10 × 38	Class CC
Rated frequency	Hz	50/60	
Max. rated voltage U_e			
• IEC/EN	V AC	690	--
• UL/CSA	V AC	600	600
Max. rated operational current I_e			
(When several devices are used next to each other, it is essential to comply with the rated load factor according to EN 60439-1 (VDE 0660-500), Table 1)			
• IEC/EN	A	32	--
• UL/CSA	A	30	30
Utilization categories		AC-22B (500 V) AC-21B (690 V, 30 A) Can only be used as fuse holder	
• IEC/EN			
• UL/CSA			
Rated conditional short-circuit current			
(type-tested with fuse links, operational class gL/gG)			
• IEC/EN	kA	100 (400 V, 500 V, 690 V)	--
• UL/CSA	kA	50 (600 V)	200
For fuse links with power losses per phase	W	3	--
Screwless wire connections			
• IEC/EN	mm ²	Cu 1.5 ... 6 (f)	
• UL/CSA	AWG	16 ... 10 (str)	

		5SG7230	3NW7430
Standards		IEC 60269-3, IEC 60269-2	IEC 60269-3, IEC 60269-2
Approvals		EN 60947-3 (VDE 0660-107), IEC 60947-3	EN 60947-3 (VDE 0660-107), IEC 60947-3
Size		D01	D02
Rated frequency	Hz	50/60	
Rated voltage U_e	V AC V DC	400 110	690 --
Rated insulation voltage U_i	V	800	
Rated impulse withstand voltage U_{imp}	kV	6	
Rated operational current I_e	A	63 ¹⁾	
Utilization categories		AC-23 A (400 V) DC-21 B (48 V) – 1 Pole DC-21 B (110 V) – 2 Pole	AC-20 DC-20
(type-tested with 3-pole, switchable version)			
Box terminals for wire connection	mm ² mm ² mm ²	Cu 1.5 ... 6 (re) Cu 1.5 ... 16 (f) Cu 1,5 ... 16 (f+AE)	Cu 1.5 ... 6 (re) Cu 1.5 ... 16 (f) Cu 1.5 ... 16 (f+AE)
Signaling switches for the display of switching positions		1 CO	1 CO
Cable terminals		Bottom	Bottom
Busbar thickness	mm	Through combination foot for 5, 10 mm	
Rated conditional short-circuit current			
(type-tested with fuse links, operational class gL/gG)	kA AC kA DC	50 8	50 --
Permissible power loss of fuse links per phase	W	5.5	3
For stand-alone operation without lateral modules or for group operation with lateral modules			

¹⁾ In the case of permanent load over 35 A, we recommend the use of 5SH5526 lateral modules. Please observe EN 60439-1, Table 1.

Selection and ordering data

	Size	Rated current	Rated voltage	Mounting width	DT	Article No.	Price per PU	PU (UNIT, SET, M)	PS*/P. unit	PG	Weight per PU approx. kg
	A		V	MW							
	NEOZED SR60 bus-mounting bases with touch protection, 3P For 5/10 mm busbars										
	27 mm wide										
	D02	63	400	1.5		5SG6206		1	4 units	031	0.175
	36 mm wide										
	D02	63	400	2		5SG6207		1	4 units	031	0.188
	NEOZED SR60 bus-mounting bases, 3P standard version For 5/10 mm busbars										
	D02	63	400	1.5		5SG6202		1	4/104 units	031	0.141
	NEOZED SR60 covers for standard version										
	D02			1.5		5SH5241		1	4/200 units	031	0.023
	Extra wide, with clearance for wiring										
	D02			2		5SH5242		1	4/140 units	031	0.027
	With double width For more clearance for wiring										
	D02			3		5SH5243		1	4/120 units	031	0.039
	For use with DIAZED screw adapters										
	DII	25	500	2.3		5SF6020		1	4 units	031	0.291
	DIII	63	500 V AC/DC (according to DIN VDE 0636-3 also 690 V AC/600 V DC)	3.2		5SF6220		1	4 units	031	0.392
	For NEOZED screw caps, NEOZED adapter sleeves and NEOZED fuse links, see chapter 5, "Fuse Systems" , "NEOZED fuse systems"										
	DIAZED SR60 bus-mounting bases, 3P standard version For use with DIAZED screw adapters										
	DII	25	500	2.3		5SF6015		1	2/52 units	031	0.210
	DIII	63	500 V AC/DC (according to DIN VDE 0636-3 also 690 V AC/600 V DC)	3.2		5SF6215		1	2/52 units	031	0.288
	DIAZED SR60 covers for standard version										
	DII			2.3		5SH2042		1	2/120 units	031	0.051
	DIII			3.2		5SH2242		1	2/120 units	031	0.056

Busbar Systems

Built-in components

Size	Rated current	Rated voltage	Mounting width	DT	Article No.	Price per PU	PU (UNIT, SET, M)	PS*/ P. unit	PG	Weight per PU approx.
A	V		MW							kg
DIAZED screw adapters with E27 thread										
Also for 5SF2 30 to 750 V										
	DII 2			▶	5SH310		1	25/1500 units	017	0.014
	4			▶	5SH311		1	25/1500 units	017	0.009
	6			▶	5SH312		1	25/1500 units	017	0.015
	10			▶	5SH313		1	25/1500 units	017	0.021
	16			▶	5SH314		1	25/1500 units	017	0.008
	20			▶	5SH315		1	25/1500 units	017	0.013
	25			▶	5SH316		1	25/1500 units	017	0.012
SR60 bus-mounting fuse holders, 3P										
For 5/10 mm busbars with screwless terminals										
	For cylindrical fuses, 10 × 38 mm  									
	-- 30	690	1.5		3NW7431		1	1 unit	031	0.185
	For UL fuses, class CC  									
	-- 30	600	1.5		3NW7431-0HG		1	1 unit	031	0.186
NEOZED SR60 bus-mounting switch disconnectors, 3P										
For 5/10 mm busbars										
	D02 63*	400	1.5		5SG7230		1	1/30 units	031	0.747
	*from 35 A load use 5SH5526 lateral module									
DIAZED screw caps, DIAZED screw adapters and DIAZED fuse links, see chapter 5, "Fuse Systems", "DIAZED fuse system"										


Other accessories

	Version	Mount- ing width	DT	Article No.	Price per PU	PU (UNIT, SET, M)	PS*/ P. unit	PG	Weight per PU approx. kg
		MW							
	Auxiliary switches for signaling the switching state for NEOZED SR60 bus-mounting switch disconnectors (5SG7230) 1 CO	0.5		5SH5525		1	1/50 units	031	0.007
5SH5 525									
	Lateral modules For greater heat dissipation for loads from 35 A with NEOZED bus-mounting switch disconnectors	0.5		5SH5526		1	5/50 units	031	0.051
5SH5 526									
	Reducers For NEOZED fuse links D01 In SR60 bus-mounting switch disconnectors			5SH5527		1	10/100 units	031	0.001
5SH5 527									

Dimensional drawings

NEOZED SR60 bus-mounting bases


D02/63 A
(a = 27 mm t = busbar thickness)



5SG6202 (t = 5 mm)

D02/63 A
(a = 27 mm, b = 50 mm)

D02/63 A
(a = 36 mm, b = 50 mm)




	a	b
E 18	27	50
E 18*	36	50
E 27	42	70
E 33 (500 V)	57	70
E 33 (690 V)	57	92
*1 1/3 wide version		

5SG6206

5SG6207


DIAZED SR60 bus-mounting bases

DII/25 A
(a = 42 mm)




5SF6014, 5SF6015
(t = 5 mm)

DIII/63 A
(a = 57 mm)



5SF6214, 5SF6215
(t = 5 mm)


DII/25 A
(a = 42 mm)



	a	b
E 18	27	50
E 18*	36	50
E 27	42	70
E 33 (500 V)	57	70
E 33 (690 V)	57	92
*1 1/3 wide version		

5SF6018, 5SF6020
(b = 70 mm)

DIII/63 A
(a = 57 mm)






5SF6218, 5SF6220
(b = 70 mm)

Built-in components


NEOZED SR60 covers

D02/63 A

5SH5241
1-fold5SH5242
1.33-fold5SH5243
2-fold


DIAZED SR60 covers

DII/25 A




5SH2042 (1-fold: a = 42 mm)

DIII/63 A




5SH2242 (1-fold: a = 57 mm)

NEOZED SR60 bus-mounting switch disconnectors/ SR60 bus-mounting disconnectors

5SG7230
3NW7430

SR60 bus-mounting fuse holders for cylindrical fuses

3NW7431,
3NW7431-0HG,