## Ø16 Round Push Button Switches (S16PR Series)

					LED block		
Туре	Appearance	Operation type	Model	Contact block C contact	DC voltage		
Extended			<b>S16PR-E1</b> □C	1	DC Voltage		
Extended button		Returned	S16PR-E1	2	_		
			S16PR-E1[]3C	3	-		
			S16PR-E2	1			
		Maintained	S16PR-E202C	2	_		
			S16PR-E2D3C	3	_		
		.X⊡ indicat		5			
		<ul> <li>※□ indicates color: </li> <li>R</li></ul>					
		Dimensions					
	S16PR-E1G	(unit: mm)					
		19.5			R0.6		
			×For p		please refer to page A-48.		
Туре	Appearance	Operation	Model	Contact block	LED block		
		type	_	C contact	DC voltage		
Extended button			<b>S16PR-E3</b> □C5		1 (5VDC)		
(illuminated)			<b>S16PR-E3</b> □C12	1	1 (12VDC)		
			S16PR-E3C24		1 (24VDC)		
			S16PR-E3□2C5		1 (5VDC)		
			S16PR-E302C12	2	1 (12VDC)		
			S16PR-E3□2C24 S16PR-E4□C5		1 (24VDC)		
			<b>S16PR-E4</b> C12	1	1 (5VDC) 1 (12VDC)		
		Maintained	<b>S16PR-E4</b> C24	-	1 (12VDC)		
			<b>S16PR-E4</b> 2C5		1 (5VDC)		
			<b>S16PR-E4</b> 2C12	2			
			<b>S16PR-E4</b> 2C24		1 (12VDC) 1 (24VDC)		
		.≫⊡ indicat			1 (24000)		
		<ul> <li>indicates color: R, B, G, Y, W</li> <li>The control unit , contact blocks, LED blocks are sold separately.</li> <li>(control unit: bold letters, contact and LED block: regular letters)</li> <li>The LED color is the same as the control unit.</li> </ul>					
		Dimensions					
		(unit: mm)					
		Panel thickness: Max. 3.5mm [Terminal Pin]					
		19.5					
		※For panel cut-out dimensions, please refer to page A-48.					

## ontrol Switche Ø16 Square Push Button Switches (S16PRS Series) Ø16 Ø22/25 Contact block LED block Operation type Туре Appearance Model Ø30 C contact DC voltage □30 S16PRS-H1DC Half guard 1 Returned S16PRS-H1D2C 2 S16PRS-H1D3C 3 S16PR S-H2DC 1 Square S16PRS-H2D2C 2 Maintained Rectangula S16PRS-H2D3C 3 Selector Switches ※□ indicates color: R, B, G, Y, W %The control unit , contact blocks, LED blocks are sold separately. Round (control unit: bold letters, contact block: regular letters) Square Dimensions (unit: mm) Rectangula S16PRS-H1G Panel thickness: Max. 3.5mm [Terminal Pin] Key Selector Switches 0.5 1.4 1.2 t<u>i</u>\_⊡≝1 Round Ę 19.5 18 ۵ 3 Square FT Rectangula Double Push Button Switches 18 13.6 R0.6 9 29.6 Mushroom-head Push Button Switches %For panel cut-out dimensions, please refer to page A-48. Contact block LED block Emergency Switches Operation Model Туре Appearance type C contact DC voltage Pilot Lights Half guard S16PRS-H3C5 1 (5VDC) (illuminated) S16PRS-H3C12 1 (12VDC) 1 Accessories S16PRS-H3C24 1 (24VDC) Returned **S16PRS-H3**2C5 1 (5VDC) Buzzers **S16PRS-H3**2C12 2 1 (12VDC) S16PRS-H32C24 1 (24VDC) S16PRS-H4C5 1 (5VDC) S16PRS-H4C12 1 (12VDC) 1 S16PRS-H4C24 1 (24VDC) Maintained **S16PRS-H4**2C5 1 (5VDC) **S16PRS-H4**2C12 2 1 (12VDC) S16PRS-H4 2C24 1 (24VDC) ※□ indicates color: R, B, G, Y, W S16PRS-H3R %The control unit , contact blocks, LED blocks are sold separately. (control unit: bold letters, contact and LED block: regular letters) %The LED color is the same as the control unit. Dimensions (unit: mm) Panel thickness: Max. 3.5mm [Terminal Pin] 0.5 1.2 1.4 19.5 18 c Œ 18 13.6 R0.6 29.6 9 %For panel cut-out dimensions, please refer to page A-48.

PUSH



PUSH

## Ø16 Rectangular Push Button Switches (S16PRT Series)

Туре	Appearance	Operation	Model	Contact block	LED block	
		type		C contact	DC voltage	
Half guard		Returned	S16PRT-H1□C	1	_	
			S16PRT-H1□2C	2	_	
			S16PRT-H1D3C	3		
		Maintained	S16PRT-H2□C	1		
			<b>S16PRT-H2</b> □2C	2	]	
			<b>S16PRT-H2</b> □3C	3		
		<ul> <li>※□ indicates color: R. B. G. Y. W</li> <li>※The control unit , contact blocks, LED blocks are sold separately. (control unit: bold letters, contact block: regular letters)</li> </ul>				
		Dimensions     (unit: mm)    Panel thickness: Max. 3.5mm				
	S16PRT-H1G					
_			×For par		lease refer to page A-48.	
Туре	Appearance	Operation	Model	Contact block	LED block	
		type		C contact	DC voltage	
Half guard (illuminated)	S16PRT-H3R	Returned	S16PRT-H3DC5	-	1 (5VDC)	
(indifinitated)			S16PRT-H3DC12	1	1 (12VDC)	
			<b>S16PRT-H3</b> □C24		1 (24VDC)	
			<b>S16PRT-H3</b> □2C5		1 (5VDC)	
			<b>S16PRT-H3</b> 2C12	2	1 (12VDC)	
			S16PRT-H3D2C24		1 (24VDC)	
			S16PRT-H4DC5		1 (5VDC)	
			S16PRT-H4DC12	1	1 (12VDC)	
			S16PRT-H4DC24		1 (24VDC)	
		Maintained	<b>S16PRT-H4</b> □2C5		1 (5VDC)	
			<b>S16PRT-H4</b> 2C12	2	1 (12VDC)	
			<b>S16PRT-H4</b> 2C24	-	1 (24VDC)	
		<ul> <li>indicates color: R, B, G, Y, M</li> <li>The control unit , contact blocks, LED blocks are sold separately. (control unit: bold letters, contact and LED block: regular letters)</li> <li>The LED color is the same as the control unit.</li> </ul>				
		Dimensions				
		• Dimensions			(unit: mm) minal Pin] <u>1.4</u> <u>6</u> lease refer to page A-48.	
					icase relet to paye A-40.	

## Ø16 Panel Cut-out Dimensions

Туре			A	В	(unit: mm) Panel Cut-out Dimensions	
Push Button Switches	Round (S16PR Series)		20	21		
	Square (S16PRS Series)		20	21		
	Rectangular (S16PRT Series)		25	21	-	
	Round (S16SR Series)		20	21		
Selector Switches	Square (S16SRS Series)		20	21		
	Rectangular (S16SRT Series)		25	21	Min. A <sup>±0.5</sup> Ø16.2	
	Round (S16KR Series)		20	21		
Key Selector Switches	Square (S16KRS Series)		20	21	Min. B <sup>40.5</sup>	
	Rectangular (S16KRT Series)		25	21		
Mushroom-head Push Button Switches (S16BR Series)		Ŷ	24	24	-	
Emergency Switches (S16ER Series)			40	40	_	
Pilot Lights	Round (L16RR Series)		20	21		
	Square (L16RRS Series)		20	21		
	Rectangular (L16RRT Series)		25	21		