Push ☐ 30 Push Button Switches

□30 Square Push Button Switches (SQ3PFS Series)

Typo	Annoaranco	Model	Contact block		LED block		
Type	Appearance	Model	A contact	B contact	AC/DC voltage	AC voltage	
Flush		SQ3PFS-P1□A(M)	1	_			
		SQ3PFS-P1□2A(M)	2	_			
		SQ3PFS-P1□3A(M)	3	_			
		SQ3PFS-P1□B(M)	_	1			
		SQ3PFS-P1 □2B(M)	_	2	_	_	
		SQ3PFS-P1 □3B(M)	_	3			
		SQ3PFS-P1□AB(M)	1	1			
		SQ3PFS-P1□2AB(M)	2	1			
		SQ3PFS-P1□A2B(M)	1	2			
	SQ3PFS-P1K□	* Dimensions * Dimensions * 30.4	Panel thickness: Ma	etters)	Singular typ Modular typ mensions, please re	e 57.4 25.0	

A-102 **Autonics**

Ø16

Туре	Appearance			Contact block		LED block		Ø22/2
			Model	A contact	B contact	AC/DC voltage	AC voltage	Ø30
Flush (illuminated)			SQ3PFS(U)-P3□AD(M)	1	_		A0 voltage	□30
			SQ3PFS(U)-P3□2AD(M)	2	_	1		Push B
		Standard	SQ3PFS(U)-P3□BD(M)	_	1		_	Switch
			SQ3PFS(U)-P3□2BD(M)	_	2			Roui
			SQ3PFS(U)-P3 ABD(M)	1	1			Squa
			SQ3PFS(U)-P3 AL(M)	1	_		1	Rect
			SQ3PFS(U)-P3□2AL(M)	2	_	_		Selecto
			SQ3PFS(U)-P3□BL(M)	_	1			Switch
			SQ3PFS(U)-P3□2BL(M)	_	2			
			SQ3PFS(U)-P3 ABL(M)	1	1			Squa
			SQ3PFS-P3□LAD(M)	1	_			Rect
			SQ3PFS-P3□L2AD(M)	2	_	_		Key Se Switch
					1	1		Rou
			SQ3PFS-P3□LBD(M)	_	2		_	Squ
	The state of the s	Arrows	SQ3PFS-P3□L2BD(M) SQ3PFS-P3□LABD(M)	1	1		1	Rec
	SQ3PFS-P3Y□	(Left/	. ,	1	1			
	SQ3PFS-P3YLI	Right)	SQ3PFS-P3□LAL(M)					Push E Switch
			SQ3PFS-P3□L2AL(M)	2	1			Mushr
			SQ3PFS-P3□LBL(M)	- C				Push E Switch
			SQ3PFS-P3 L2BL(M)	7///	2			Emerg
			SQ3PFS-P3□LABL(M)	1	1			Switch
	SQ3PFSU-P3Y□ SQ3PFS-P3YU□	Arrows (Up/ Down)	SQ3PFS-P3 UAD(M)	1	_	1	_	Pilot L
			SQ3PFS-P3 U2AD(M)	2	_			Acces
			SQ3PFS-P3 UBD(M)	_	1			710000
			SQ3PFS-P3 U2BD(M)	_	2			Buzzers
			SQ3PFS-P3 UABD(M)	1	1			Buzzers
			SQ3PFS-P3 UAL(M)	1	_		1	
			SQ3PFS-P3 U2AL(M)	2	_			
			SQ3PFS-P3□UBL(M)	_	1			
			SQ3PFS-P3 U2BL(M)	_	2			
			SQ3PFS-P3□UABL(M)	1	1			
		 ※□ indicates color: , , , , , , , , , , , , , , , , , , ,						
		Dimension	ns				(unit: mm)	
		48.1	98	Panel thickness	B	Singular type Modular type		
			3.7				57.4 25.0	

Autonics A-103

□30 Pilot Lights (LQ3RF Series)

Туре	Appearance	Madel	Contact block	Contact block		LED block			
		Model	A contact	B contact	AC/DC voltage	AC voltage			
Flat square (flush)		LQ3RF-L4 □D(M)			1	_			
		LQ3RF-L4□L(M)		_	_	1			
		The M in the model na block.The light unit and LED	 ※☐ indicates color: R, B, G, Y, W ※The M in the model name indicates modular type LED block. Models without M are singular LED block. ※The light unit and LED blocks are sold separately. (light unit: bold letters, LED block: regular letters) ※The LED color is the same as the control unit. 						
		Dimensions	Panel thickness	:: Max. 6mm		(unit: mm)			
	LQ3RF-L4B□	2.8	382	394		A B			
		30.4		В	Singular ty				
		₹ 50.4	3.7 A	-	inodulai tyj	20.0			

□30 Panel Cut-out Dimensions

		→	→	3.7	<u>^</u>	medalai type erri zele		
					※For panel cut-out dimension	ons, please refer to page A-104.		
□30 Panel Cut-out Dimensions (unit: mm)								
Туре		TTP	A	В	Panel Cut-out Dim	ensions		
Square Push B (SQ3PFS Serie	outton Switches es)		45	55		Ain. A ^{±0.5}		
Pilot Lights (LQ3RF Series)		37	55		Min. B ^{±0.5}		

A-104 **Autonics**