



Main

Range of product	Modicon Easy M100
Product or component type	Logic controller
[Us] rated supply voltage	100...240 V AC
Discrete input number	24 DC input (4 fast input) conforming to IEC 61131-2 Type 1 discrete input
Discrete output type	Relay normally open
Discrete output number	16 relay
Discrete output voltage	100...250 V AC 5...30 V DC
Discrete output current	2 A

Complementary

Discrete I/O number	40
Supply voltage limits	85...264 V
Network frequency	50/60 Hz
Inrush current	≤ 50 A
Power consumption in VA	≤ 16 VA at 100...240 V
Discrete input logic	Sink or source (positive/negative)
Discrete input voltage	24 V
Discrete input voltage type	DC
Voltage state 1 guaranteed	≥ 15 V for input
Current state 1 guaranteed	≥ 2.5 mA for input
Voltage state 0 guaranteed	≤ 5 V for input
Current state 0 guaranteed	≤ 1.5 mA for input
Discrete input current	7 mA for input
Input impedance	3.3 kOhm for discrete input
Response time	10 ms during turn-off operation for output with Q0...Q15 terminal(s) 10 ms during turn-on operation for output with Q0...Q15 terminal(s) 125 μ s during turn-off operation for input with I14...I23 terminal(s) 55 μ s during turn-on operation for input with I14...I23 terminal(s) 100 μ s during turn-off operation for input with I8...I13 terminal(s) 35 μ s during turn-on operation for input with I8...I13 terminal(s) 5 μ s during turn-off operation for fast input with I0, I1, I6, I7 terminal(s) 5 μ s during turn-on operation for fast input with I0, I1, I6, I7 terminal(s) 100 μ s during turn-off operation for input with I2...I5 terminal(s) 35 μ s during turn-on operation for input with I2...I5 terminal(s)
Configurable filtering time	12 ms during input 3 ms during input 0 ms during input
Output voltage limits	250 V AC 30 V DC
Current per output common	4 A at COM 3 terminal 4 A at COM 2 terminal 4 A at COM 1 terminal 4 A at COM 0 terminal
Electrical durability	Resistive DC-12, 24 V / 48 W : 100000 cycles Resistive AC-12, 240 V / 480 VA : 100000 cycles
Switching frequency	0.1 Hz with maximum load
Mechanical durability	≥ 20000000 cycles for relay output
Minimum load	10 mA at 5 V DC for relay output
Memory capacity	256 kB internal flash memory with 10000 instructions for backup of programs

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Data storage equipment	32 GB micro SD card (optional)
Battery type	BR2032 Li-CFx (Lithium-Carbon Monofluoride), battery life: 4 yr
Backup time	3 years at 25 °C by interruption of power supply
Execution time for 1 KInstruction	0.3 ms for event and periodic task
Execution time per instruction	0.2 µs Boolean
Exct time for event task	60 µs response time
Clock drift	<= 90 s/month at 25 °C
Regulation loop	Adjustable PID regulator up to 14 simultaneous loops
Control signal type	CW/CCW signal at 100 kHz for fast input (HSC mode) Single phase signal at 100 kHz for fast input (HSC mode) Pulse/Direction signal at 100 kHz for fast input (HSC mode) Quadrature (x1, x2, x4) signal at 100 kHz for fast input (HSC mode)
Counting input number	4 fast input (HSC mode) (counting frequency: 100 kHz) 32 bits
Integrated connection type	Non isolated serial link "serial 2" terminal block and interface RS232/RS485 Non isolated serial link "serial 1" terminal block and interface RS485 USB port mini B USB 2.0
Transmission rate	12 Mbit/s - communication protocol: USB 1.2...115.2 kbit/s (115.2 kbit/s by default) for bus length of 3 m - communication protocol: RS232 1.2...115.2 kbit/s (115.2 kbit/s by default) for bus length of 15 m - communication protocol: RS485
Communication port protocol	Non isolated serial link : Modbus protocol with master/slave method - RTU/ASCII or SoMachine-Network USB port : USB protocol - SoMachine-Network
Local signalling	1 LED per channel green for I/O state 1 LED green for SL1 1 LED green for SD card access (SD) 1 LED red for module error (ERR) 1 LED green for RUN 1 LED green for PWR
Electrical connection	Mini B USB 2.0 connector for a programming terminal Fixed screw terminal block, 4 terminal(s) for connecting the serial link1 Fixed screw terminal block, 3 terminal(s) for connecting the 24 V DC power supply Fixed screw terminal block for outputs Fixed screw terminal block for inputs
Cable length	<= 150 m unshielded cable for output <= 10 m shielded cable for high speed input <= 10 m shielded cable for fast input <= 50 m unshielded cable for input
Insulation	1780 V AC between supply and internal logic 1780 V AC between output groups 1780 V AC between output and internal logic Non-insulated between inputs 560 V AC between input groups 560 V AC between fast input and internal logic 560 V AC between input and internal logic
Mounting support	Plate or panel with fixing kit top hat type TH35-7.5 conforming to IEC 60715 Rail top hat type TH35-15 conforming to IEC 60715
Height	90 mm
Depth	70 mm
Width	175 mm
Product weight	0.409 kg

Environment

Standards	EN/IEC 61131-2 EN/IEC 61010-2-201
Product certifications	CSA CULus IACS E10 RCM
Marking	CE
Electromagnetic compatibility	Conducted RF disturbances (test level: 10 V - 0.15...80 MHz) conforming to EN/IEC 61000-4-6 1.2/50 µs shock waves immunity test (test level: 1 kV - relay output) conforming to EN/IEC 61000-4-5 1.2/50 µs shock waves immunity test (test level: 1 kV - power lines (AC)) conforming to EN/IEC 61000-4-5 1.2/50 µs shock waves immunity test (test level: 0.5 kV - power lines (DC)) conforming to EN/IEC 61000-4-5 1.2/50 µs shock waves immunity test (test level: 1 kV - shielded cable) conforming to EN/IEC 61000-4-5 1.2/50 µs shock waves immunity test (test level: 1 kV - I/O) conforming to EN/IEC 61000-4-5 1.2/50 µs shock waves immunity test (test level: 2 kV - relay output) conforming to EN/IEC 61000-4-5 1.2/50 µs shock waves immunity test (test level: 2 kV - power lines (AC)) conforming to EN/IEC 61000-4-5 1.2/50 µs shock waves immunity test (test level: 1 kV - power lines (DC)) conforming to EN/IEC 61000-4-5 Electrical fast transient/burst immunity test (test level: 1 kV - serial link) conforming to EN/IEC 61000-4-4 Electrical fast transient/burst immunity test (test level: 1 kV - I/O) conforming to EN/IEC 61000-4-4 Electrical fast transient/burst immunity test (test level: 2 kV - relay output) conforming to EN/IEC 61000-4-4 Electrical fast transient/burst immunity test (test level: 2 kV - power lines) conforming to EN/IEC 61000-4-4 Magnetic field at power frequency (test level: 30 A/m conforming to EN/IEC 61000-4-8 Radiated emission (test level: 47 dBµV/m QP, class A - 10 m) conforming to EN/IEC 55011 Radiated emission (test level: 40 dBµV/m QP, class A - 10 m) conforming to EN/IEC 55011 Conducted emission (test level: 73 dBµV/m QP/60 dBµV/m AV - power lines (AC)) conforming to EN/IEC 55011 Conducted emission (test level: 79 dBµV/m QP/66 dBµV/m AV - power lines (AC)) conforming to EN/IEC 55011 Susceptibility to electromagnetic fields (test level: 10 V/m - 80 MHz...3 GHz) conforming to EN/IEC 61000-4-3 Electrostatic discharge immunity test (test level: 6 kV - contact discharge) conforming to EN/IEC 61000-4-2 Electrostatic discharge immunity test (test level: 8 kV - air discharge) conforming to EN/IEC 61000-4-2
Immunity to microbreaks	10 ms
Ambient air temperature for operation	0...55 °C for horizontal installation
Ambient air temperature for storage	-25...70 °C
Relative humidity	10...95 % without condensation in storage 10...95 % without condensation in operation
IP degree of protection	IP20 with protective cover in place
Pollution degree	<= 2
Operating altitude	0...2000 m
Storage altitude	0...3000 m
Vibration resistance	3 gn (vibration frequency: 8.4...150 Hz) on panel mounting 3.5 mm (vibration frequency: 5...8.4 Hz) on panel mounting 1 gn (vibration frequency: 8.4...150 Hz) on symmetrical rail 3.5 mm (vibration frequency: 5...8.4 Hz) on symmetrical rail
Shock resistance	30 gn (test wave duration:11 ms) 15 gn (test wave duration:11 ms)